

# SPP-R410

## 4 inch Mobile Printer




# Compact and Rugged



Compatible with



Made for iPod iPhone iPad



NFC



### Seamless Connectivity Options

- Wide-range Wi-Fi connectivity supported (WLAN 802.11a/b/g/n(5GHz and 2.4GHz dual-band support))
- Smart Wi-Fi setting (Soft AP) via mobile device
- Wide-range Wi-Fi connectivity supported (WLAN 802.11a/b/g/n(5GHz and 2.4GHz dual-band support))

### Enhanced Optimization for Field Service

- Compact, ergonomic and light-weight (530g)
- 1.8 m / 6 ft. drop rate
- IP54 (Printer only) water and dust proof
- 56-hour stand by time once fully charged (Bluetooth model in power save mode)
- Supports continuous printing - 6 rolls of 57 mm diameter paper (Total 162 m) once fully charged
- Supports a wide range of carrying and charging accessories

### Multi-Functional

- Fast printing speed up to 90 mm/sec (Receipt)
- Transmissive gap sensor - supports front and back sensors
- Easily switch from receipt to label printing using feed button or VMSM software (No hardware change needed)
- Supports linerless label printing (optional)

Made for iPod iPhone iPad



# SPP-R410

## 4 inch Mobile Printer



Reported by Chunichisha

## Specifications

### Printer Specifications

#### Print Method

Direct Thermal

#### Print Speed

Up to 90 mm/sec (Receipt)  
Up to 60 mm/sec (Linerless)  
12.5% pattern

#### Print Resolution

203 dpi

#### Print Width

Up to 104 mm

#### Sensor

Paper End  
Paper Cover Open  
Black Mark

### Media Characteristics

#### Media Type

Receipt, Label, Linerless (Optional)

#### Media Width

112 mm / 105 mm (Optional)

#### Media Roll Diameter

Up to 57 mm

#### Media Thickness

0.07 ± 0.005 mm

#### Supply Method

Easy Paper Loading

### Physical Characteristics

#### Dimensions (WxD)

143.0 x 138 x 66 mm  
(5.63 x 5.44 x 2.60 inch)

#### Weight

Including battery: 530 g (1.17lbs)  
Paper: 242 g (0.53 lbs)

#### Battery

7.4 V Li-ion, 2,600 mAh,  
Rechargeable Charging time: Up to 4.0 hrs

### Performance Characteristics

#### Memory

64 Mbit SDRAM, 32 Mbit FlashROM

#### Interface Options

Standard: USB V2.0 FS + Serial  
Optional: USB V2.0 FS + Serial + Bluetooth V4.1  
(Classic + LE) / WLAN 802.11a/b/g/n  
(Infrastructure, Ad-hoc, Wi-Fi Direct,  
SoftAP) - WEP40/104, WPA1/2(PSK,  
EAP)

### Environment Characteristics

#### Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)  
Storage: -30 ~ 70°C (-22 ~ 158°F)

#### Humidity

Operating: 10 ~ 80% RH

#### Sealing

IP54

#### Drop Rate

1.8 m (6 ft.)

### Software

#### Emulation

BXL / POS

#### Driver / Utility

Windows Driver, OPOS/JPOS Driver,  
Linux CUPS Driver, Utility Program

#### SDK

iOS SDK, Android SDK, Windows SDK, Linux SDK

### Fonts / Graphics / Symbologies

#### Character Size

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24  
KOR, CHN, JPN: 24 x 24

#### Characters Per Line

Font A: 69 Font B, C: 92  
KOR, CHN, JPN: 34

#### Character Sets

Alphanumeric: 95  
Expanded Graphics: 128 x 33 page  
International: 32

#### Graphics

Supporting user-defined fonts, graphics,  
formats, layouts, and logos

#### Barcode

1D: Codabar, Code 39, Code 93, Code 128,  
EAN-8, EAN-13, ITF, UPC-A, UPC-E  
2D: Aztec, Data Matrix, GS1 Databar, MaxiCode,  
PDF417, QR code

### Accessories

#### Standard

Belt Clip, Battery Pack, Battery Charger,  
Power Cord, Paper

#### Optional

Belt Strap, Shoulder Strap, Single Battery Cradle,  
Quad Battery Charger, Cigarette Lighter Charger,  
Serial/USB Cable, Cleaning Pen



BR-SPP-R410-EN-MAR17-V3-NF

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

**BIXOLON**®

**BIXOLON Co., Ltd.**  
+82 (0) 31 218 5500  
sales@bixolon.com

**BIXOLON America Inc.**  
+1 858 764 4580  
sales@bixolonusa.com

**BIXOLON Europe GmbH**  
+49 211 68 78 54 0  
sales@bixolon.de

www.Bixolon.com

