


Line Matrix Printers

6800 Series



Key Applications

- Barcoding
- Invoices
- Delivery notes
- Packing lists
- Crystal reports
- Labels
- Multi-lingual printing

Features:

- Modular enclosure occupying smaller footprint
- New user interface with larger LCD screen, graphical display and intuitive menu navigation
- Remote printer diagnostics to monitor printer status and configure settings & firmware
- PowerPrint™ delivers improved print quality on multi-part forms
- Lowest cost of ownership
- Backwards-compatible cartridge ribbons reduce inventory management costs
- Energy efficient technology lowers idle power consumption and boosts operating efficiency

Specifications*:

Printer Model	: 6805	6810	6815
Printing Technology	: Line matrix impact printer, 136 column		
Print Speed¹ (LPM) - Upper Case/ Lower Case	:		
- HSD	500/428	1000/856	1500/1289
- DP	375/300	750/600	1125/900
- NLQ	200/154	400/306	600/459
Graphics Speed (Inches (mm) per minute)	:		
- 60 x 48 dpi	63 (1600)	125 (3175)	187 (4750)
- 60 x 72 dpi	42 (1067)	83 (2108)	127 (3226)
- 90 x 96 dpi	21 (533)	42 (1067)	61 (1549)
Paper Feed Speed (Inches (mm) per sec.)	: 12 (305)	20 (508)	25 (635)
Character Pitch (Character per inch)	: 5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1 and 20		
Line Spacing (Lines per inch)	: 1.5, 2, 3, 4, 5, 6, 7, 9, 10 and 12		
Graphics Resolution	: 240 dpi horizontal, 288 dpi vertical (max.)		
Barcodes	: code 39, code 128, Interleaved 2 of 5, UPC-A, UPC-E, EAN 8, EAN 13, EAN 128, codabar, MSI, PDF-417, Postnet, Intelligent Mail Barcode (IMB)		
Fonts	: Draft, Data Processing, Courier, Gothic, OCR A, OCR B		
Character Sets	: 47 Language and 43 Character Sets		
Character Styles	: Bold, Italic, Superscript, Underline, Overline, Strike-through		
Paper type/ Media width	: Continuous, Fan-folded, Edge-perforated, 3 to 17 inches (76 to 432 mm) wide, 2 to 12 inches (5.08 to 30.48 cm) long		
Paper Handling	: Straight paper path with easy-load adjustable tractors, paper-out detection & alarm, paper-motion detection & alarm		
Print Width	: 13.6 inches (345 mm)		
Stationery[#]	: up to 6 part, 56 to 163 GSM, up to 0.64 mm thickness		
Ribbon Life (standard)	: 9,000 Pages (Page yield based on ISO LSA page)		
Emulations	: Tally ANSI, Genicom ANSI, P5000/P600/P6000, Epson FX-1180, IBM Proprinter, MTPL (Tally Dit Mtrix), PGL (TG Version), QMS Code V, Tally Industrial Graphics, PCL-3, HP-2564C, DEC LG01		
Connectivity/ Interfaces	: Standard USB 2.0, Serial RS-232 and Ethernet 10/100 BaseT Optional - Parallel - IEEE-1284-Centronics		
Acoustic (dBA)	:		
- Pedestal	60.5	NA	NA
- Cabinet	50	50	52
MTBF	: 10,000 hrs at 25% duty cycle & 25% page density		
Dimensions (unpacked)	:		
- Pedestal	H 920 mm x W 640 mm x D 530 mm		
- Cabinet	H 1070 mm x W 640 mm x D 530 mm		
Weight (unpacked)	:		
- Pedestal	57 Kg	NA	NA
- Cabinet	73 Kg	73 Kg	87 Kg
Power Supply	: 220/240 VAC ± 10%, 50 Hz ± 2%		
Power Consumption (Typical)	: 180W	260W	310W
	7W (Energy save mode)		
Software/ Drivers	: PrintNet enterprise remote management software, SAP device support, Windows XP, Windows Vista, Windows 7, Windows 8.1, Windows 10, Windows 2000 Server, Windows 2003 Server, Windows 2008 Server, Windows 2008 Server R2, Linux, AIX, SAP		
Consumables (options)	: (Page yield based on ISO LSA page)		
- Premium Life Cartridge Ribbon	- 17,000 pages		
- Extended Life Cartridge Ribbon	- 30,000 pages		
Compliance	: RoHS Compliant, Safety : BIS approved		

- Paper is highly variable medium & should be tested prior to bulk use. All trademarks are registered trademarks of their respective companies.

* Specifications are subject to change without prior notice. 1 - Print speed depends on combination of fonts & line pitch.

Lipi Data Systems Ltd

1, Mittal Chambers, Nariman Point, Mumbai 400 021, India

T: +91 22 2288 2960

E: contact@lipi.in W: www.lipi.in

An ISO 9001:2015, ISO 14001:2015 & ISO 45001:2018 certified company.

