


Direct Thermal Label Printer

LD 43E



Key Applications

- Inventory Labels
- Asset Labels
- Packing Slips
- Price Labels
- POD Labels
- Lab & Specimen Labels
- Shipping Labels

Features:

- Print speed of 150mm /sec
- Direct thermal printing mechanism
- Ethernet & USB Interface
- Use with any direct thermal label
- Easy setup

Industries:

- Retail
- Manufacturing
- E-commerce
- Healthcare
- Warehouse & Logistics

Specifications*:

Printing Method	: Direct thermal
Resolution	: 203 dpi
Print Speed	: 150mm /s
Paper Width	: 25mm to 112mm
Printing Width	: Max 108mm
Max. Print Length	: 3000mm
Media Width	: 25 mm to 112 mm
Paper Thickness	: 0.08 - 0.2 mm
Media Type (Labels)	: Continuous gap, black mark, and punched hole
Label Length	: 300mm
Memory	: 384KB Flash+96KB SRAM+4MB PSRAM
Internal Fonts	: ANK Font A/B; Simplified/Traditional fonts
Sensors	: Reflective sensor, Transmission gap sensor
Command / Emulation	: Provided, TSC Command
1D Barcode	: Codabar, Code11, Code39, Code93, Code128, EAN8, EAN13, Interleaved 2-of-5, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), UPC
2D-Barcode	: PDF417, Data Matrix, QR Code
Power Input	: AC 100–240 V, 1 A, 50/60 Hz
Power Output	: DC 24 V, 2 A
Interface	: USB + Ethernet
Driver / OS support	: Windows, Android, iOS
Operating Environment	: 5~40 ° C, 20~90 %
Storage Environment	: -25~55 ° C, 20~93 %
Dimension (LxWxH)	: 225 mm X 177 mm X 168 mm
Weight	: 1.1 Kg (Approx.)
Print Head Life	: 100 KM
Compliance & Safety	: RoHS Compliant, Safety : BIS approved

* Specifcaions are subject to change without prior notice

Lipi Data Systems Ltd

1, Mittal Chambers, Nariman Point, Mumbai 400 021, India

T: +91 22 2288 2960 / 6390 2200

E: contact@lipi.in W: www.lipi.in

An ISO 9001, ISO 14001, ISO 45001, ISO 27001 & ISO 20000-1 certified company.

