


Thermal Receipt Printer

LR 30E



Key Applications

- Retail POS Receipts
- Supermarket Receipts
- Restaurant KOT / Bills
- Hospitality Receipt / Bills
- Tokens
- Ticket Printing

Features:

- 200 mm/s low noise, high-speed printing
- Supports cash drawer control
- High quality clear prints
- Powerful graphic & character customization commands for clear, active printing
- Supports various 1D barcode & QR code printing

Industries:

- Supermarket
- Restaurant
- Cafe
- E-commerce
- Retail
- Warehouse & Logistics

Specifications*:

Printing Method	: Direct thermal
Resolution	: 203 dpi
Print Speed	: 200 mm /s
Paper Width	: 79.5 mm $\pm$ 0.5mm
Print Width	: 72 mm
Column Capacity	: 80mm paper: Font A - 42 columns or 48 columns / Font B - 56 columns or 64 columns
Paper Type	: Thermal paper 79.5 mm X 80 mm (MAX)
Paper Thickness	: 0.06 ~ 0.08 mm
Roll Diameter (Max.)	: 80mm
Core Diameter (Min.)	: 13mm
Paper Loading Method	: Simple paper loading
Paper Cutting Method	: Auto full cut
Supporting Function	: out-of-paper alarm
Interface	: USB + Ethernet
Emulation	: ESC
Driver / OS Support	: Windows, Android, iOS
Cash Drawer Control	: DC24V, 2A, 6-wire RJ-12
Dimension (LxWxH)	: 168 mm X 133 mm X 124 mm
Weight	: 1.5 Kg (Approx.)
Thermal Head Life	: 100 km
Cutter life / reliability	: 1 million cuts
Compliance & Safety	: RoHS Compliant, Safety : BIS approved
Power Supply / Adaptor	: Input: 100-240VAC, 50-60Hz, Output: DC 24V / 2A
Power Input	: DC24V, 2A
Operating Temperature / Humidity	: 0~50 °C, 10~80 % non-condensing
Storage Temperature / Humidity	: 20~60 °C, 10~90 % non-condensing

* Specificaions are subject to change without prior notice

Lipi Data Systems Ltd

1, Mittal Chambers, Nariman Point, Mumbai 400 021, India

T: +91 22 2288 2960 / 6390 2200

E: contact@lipi.in W: www.lipi.in

An ISO 9001, ISO 14001, ISO 45001, ISO 27001 & ISO 20000-1 certified company.

